

PDXT SERIES SPEEDGATE

time sensitive security



The PDXT Series Trackless SpeedGate is the perfect combination of speed and security.

With an open or close cycle-time of less than 7 seconds, the PDXT Series Trackless SpeedGate ensures minimal site exposure; virtually eliminating tailgating.

FEATURES

- Rapid cycle-time
- Electromechanically driven
- Patented design
- Minimal footprint and operational clearance required
- Robust construction
- Factory assembled and tested
- Integrated drive units
- Single-source supplier

BENEFITS

- Reduced site exposure
- Easily integrated into existing site plan
- Easy to install
- Extremely low maintenance
- Reliable
- Reduces idling time
- Maximum throughput reduces security risk

WALLACE
INTERNATIONAL

BUILT TO WITHSTAND

PDXT SERIES SPEEDGATE


time sensitive security



Trackless gate with razor wire



Trackless gate



Custom panel infill options



Trackless

TECHNICAL SPECIFICATIONS

Rapid open or close cycle-time of less than 7 seconds reduces security risk

Fully galvanized construction makes for a durable product

Gate is shipped factory tested, assembled ready for a fast and easy install, reducing site exposure and operational downtime

PLC controlled for easy programming and integration into any perimeter security system

Panel infill options available to match gate system look or aesthetic into overall architectural design

UL 325 Listed (class 1,2,3 & 4)

STANDARD FINISH

Galvanized

Custom powder-coated colors available on request

OPTIONS

Tailgate Detection and Anti-Tailgate Logic

Uninterruptable Power Supply (UPS)

Traffic Lights (bidirectional)

Safety Photo Cell

Strobe Light

Detection Loops

Hot or Cold-Weather Kit

Custom control consoles

TECHNICAL DATA	UNIT	PDXT TOP TRACK	PDXT TRACKLESS
Voltage	H	208 - 240V	208 - 240V
Frequency			
Current	G		
Duty Cycle	B	C	C
Max. Clear Drive Thru Height	Feet (m)	20' (6)	Unlimited
Max. Clear Drive Thru Width	Feet (m)	24' (7)	20' (6)
Max. Gate Panel Height	Feet (m)	20' (6)	8' (2.5)
Gate Infill	Panel Infill	Up to Solid Panel	Vertical Bar/Welded Wire
Finish	Coating	Galvanized and/or Powder-Coated	Galvanized and/or Powder-Coated
Operating Temp Range	°F (°C)	-40 to +120 (-40 to +49)	-40 to +120* (-40 to +49)

*Ventilation kits recommended for temperatures over 120 F



DISTRIBUIDOR EN MÉXICO

Alse Mexicana SA. de CV.
Av. Beethoven #5330, Fracc. La Estancia,
Zapopan, Jalisco. México. CP. 45030

Tel.+52(33) 3121-7878
Lada sin costo: 01800-001-2573
info@alsemexicana.com
www.alsemexicana.com