P110/P550 | Plug Lockout User Manual

Material Content:

a. Plug Lockout Small P110

b. Self-adhesive Label

P110:





a. Plug Lockout Large P550

b. Self-adhesive Label

Security Tech Germany

P550:

- For standard power plugs up to approx. 550V
- Cable diameter: 25 mm (1")
- Inner diameter: 74 mm (7")



For standard 110/220V power plugs

Cable diameter: 12 mm (0,5")
Inner diameter: 42 mm (3,5")

1. Remove the plug from the socket. Open the plug lockout device and insert the plug inside with the cable in the cable opening.



2. Close the plug lockout device.



- 3. Insert at least one padlock into one of the holes provided and lock it.
- 4. Check whether the plug is securely locked by pulling on the cable.
- If the plug can be pulled out through the side opening of the cable, the selected lock device is not suitable for the plug. In this case, please use the smaller size (see above).



Please note that the P110 and P550 plug lockout device may also be suitable for other plug types such as compressed air plugs or hose connections. It is important in this case that the plug or connection cannot be pulled through the side opening of the device. It should remain securely locked in the lock device.

WARNING:



Product should only be used by personnel properly trained in lockout procedures. Product should only be used on the appropriate application (s). Follow product instructions for proper application of each product. Properly trained personnel should check to ensure that product is secure and equipment will not operate. Failure to follow product instructions and warnings may result in serious bodily inury or death.

You will find additional notes and corresponding application videos to every lockout device following the link: http://www.abus.com/eng/Service/Videos/Industrial-safety